

# COUPLING/DECOUPLING NETWORK



# FCC-801-USB-3.0

## Specifications

Application:	IEC 61000-4-6 Conducted Immunity
Frequency:	150 kHz – 230 MHz
Input/Output Lines:	9
Impedance:	Frequency dependent 150 kHz – 26 MHz: $150 \Omega \pm 20 \Omega$ 26 MHz – 80 MHz: $150 \Omega + 60 \Omega - 45 \Omega$ Published IEC 61000-4-6, Table 3 80 MHz – 230 MHz $150 \Omega + 60 \Omega - 60 \Omega$ Published IEC 61000-4-6, Annex B Table B.1
Maximum Current:	3A
Maximum Voltage:	250 VAC 250 VDC
RF Disturbance Port:	
Power Rating:	9 Watts max
EUT/AE Port Connector:	USB Type A or B (Active Pins 1-9)
RF Disturbance Port:	50 $\Omega$ BNC
Dimensions (L x W x H):	31 cm x 18 cm x 15 cm
Weight:	3.2 kg

# FCC

Fischer Custom Communications, Inc.

19220 Normandie Ave., Unit B Torrance, CA 90502  
Phone: 310-303-3300

Email: [sales@fischercc.com](mailto:sales@fischercc.com)

© Fischer Custom Communications, Inc.